



...digital radio on the move

INSTALLATION & USER GUIDE

Designed and
Engineered
in the UK. 

DAB DAB+

DIGITALRADIO

digitalradio 

What's in the pack?

Remote Key:

1 - Menu	4 - Station Left	7 - Pre-set Down
2 - Add/Delete	5 - OK	8 - Scan
3 - Pre-set Up	6 - Station Right	9 - On/Off



Getting Started - Initial Setup of Head Unit

- On first install, the AutoDAB controller will default to transmitting on 87.5MHz. Tune the car radio to this frequency.
- The car radio will display '**AutoDAB**' and the audio message '**Scanning AutoDAB, please wait**' will be heard.
- The audio message repeats every 5 seconds.
- Choose a preset on the car radio and store the AutoDAB frequency to it.

Pairing a Remote

- To pair remote press '**Menu**' and '**On/Off**' together for two seconds. A short beep will be heard confirming your device has been paired.
- Next press '**Menu**' to start the digital radio. After a short delay the car radio will display the first available digital radio station found e.g. *Absolute*

Browsing through Pre-set Stations

- Your AutoDAB will come with pre-sets already loaded. To browse through your pre-sets, simply use the 'Pre-set Up / Down'

Scanning for Stations

- To update the available station in your current location, press 'Scan' and the audio message 'Scanning will repeat twice.
- After around 30 seconds, the car radio will display the total number of DAB stations found.

Navigating the Station List (Alphabetical)

- Press '**Station Left/Right**' to move up or down the station list from the current tuned station.
 - **Tip** - If you are looking for a specific station, then go to the pre-set nearest to it in the alphabet and move up and down from there.

Adding/Deleting Pre-sets

- When you locate a station that you want to add or delete from your pre-sets, simply press '**Add/Del**'.
- If the pre-set is not already in your pre-set list, then the station will be added, and the voice confirmation '**Pre-set Added**' will be heard.
- If the pre-set is already included within your list, then it will delete the pre-set and the voice confirmation '**Pre-set Deleted**' will be heard.

Set Browse	AutoDAB can be navigated in either List mode (all available stations listed alphabetically A to Z or in Ensemble mode (all stations listed by ensemble i.e. a group of stations that are transmitted together).
Set Frequency	Allows user to adjust the FM freq. which the AutoDAB broadcasts on. The default is 87.5MHz.
Set Voice Volume	The voice prompt can be increased by pressing ' Pre-set Up ' and decreased by pressing ' Pre-set Down '. The voice volume level is displayed as a figure between 01 to 10 max.
Announcement	You can select to receive either all announcements when broadcast, just traffic and alarm, or turn them all off.
Factory Reset	Restore the AutoDAB tuner to factory settings. All the pre-sets/stations will be deleted and the AutoDAB will be reset to its original configuration.

How to fit - PLUG



- Remove all the contents from the AutoDAB box
- Position the antenna in the top right of the front windscreen (top left for right hand drive cars). The antenna should be located parallel to the A-pillar of the car (FIG 1). We recommend that it is held in position with a temporary fix until you confirm that you have a good reception.
- Plug the cigarette lighter charger into the nearest 12v supply to where you want to locate the AutoDAB box – the red light should illuminate.
- Plug the 3.5mm Jack into the cars aux-in socket. (if required)
- Now plug all connections into the AutoDAB box (FIG 2)




FIG 2

